



2-45DTM TRUCK MOUNTED SHOTBLASTER

2-45DTM TRUCK MOUNTED SHOTBLASTER



The Blastrac 2-45DTM shot blaster is the workhorse of the horizontal blast cleaning machine equipment line. The 2-45DTM is completely self-contained and is ideal for surface preparation specialists, doing jobs with limited downtime allowed for jobs such as airports, roads, motorways (highways), bridges, ramps and many more. The 2-45DTM is a shot blaster that is delivered "turn key" and is very user and environmentally friendly.

CABIN

All important processes are carried out by the machine operator, working from an enclosed cab from where he is able to control everything, with one user friendly touch screen. Every single blast head operational function can be manipulated by the combination of a touch screen and joystick panel. This system is designed to make the operating of this total concept as easy as possible. Once all the settings, for example the drive speed and blast pressure, are set to the ideal for the surface to be treated, it's simply a matter of pushing 2 buttons and the truck starts driving and blasting as the previous setting.

DUST CONTROL

While blasting large surfaces, big quantities of debris are produced, depending on the surface, concrete or asphalt and the grade of pollution. Debris production can vary between 1 and 2 tons per hour. Due to a sophisticated magnetic separation system the 2-45D shot blast machine is able to automatically separate the generated dust from the steel shot to reuse it again. When the dust is separated in the blast head the dust will be sucked away by a very powerful dust collector, "The 2-45TDC" through the connected hoses. This dust collector is equipped with 24 pieces of specially designed high quality Blastrac cartridge filters to separate the debris for further internal transport. Due to new technology used in this new concept of dust collector it is able to transport all generated debris directly into 2 Big Bag's. This is a continuous process, even while changing the big bags, the blast head keeps doing its job. In the rear of the truck is a place for 8 to 10 pieces of 1 ton big bags, which means a non-stop working time of up to 8 hours, without having to stop the shot blasting production.





ENGINE & HYDRAULICS

The BLASTRAC 2-45DTM has side shift. During blasting or from stand still it is possible to shift the blast head from the total left side to the total right side, outside the reach of the wheels of the truck. This enables blasting as close to the sides as is possible. The 2-45DTM is powered by a 6 cylinder, 10.8 litre, diesel engine, and is equipped with the most modern hydraulic and electronic technologies. The 2-45DTM is a hydrostatically driven unit for a perfectly homogenous result.

TRANSPORTATION

Speciality contractors can drive to the job with all equipment, personnel and supplies safely in a single vehicle. All controls, dust collection, spares, consumables and blast head, are protected in an enclosed truck body. The first thing to do is unload the Blastrac 2-45D blast head that is stored and secured by a wheel lock system, heavy load binders and straps in the back of the truck. Use the tail lift which is a specially made for heavy loads and has a long lifting plate with special tools to secure the blast unit. Suction hoses are placed very easily due to a very efficient storing and mounting system.



CONNECTING THE SIDE SHIFT AND BLAST HEAD

Once the blast head is positioned in front of the adaption plate on the front of the truck you only have to connect four hydraulic hoses and one electrical connector. The quick attach system takes care of an easy and safe connection of the complete side shift and blast unit onto the adaption plate of the truck. All that is needed is to push one button on the touch screen panel and secure the connection with heavy sliding bolt system.



AUTOMATIC SWEEPER

Blastrac 2-45TBS is a fully automatic tow behind sweeper for the use in combination with the 2-45DTM truck mounted shot blast unit. The 2-45TBS is equipped with the latest technologies and safety requirements.

SAFETY

The BLASTRAC 2-45DTM is equipped with the latest technology regarding safety. There are dead man switches located inside the cabin as well as 2 pieces inside the truck body. Because of the low noise level it's not necessarily to where ear protection in the cabin. In front of the truck there's a double flashing light bar for traffic approaching in opposite direction. Latest technology of flash lights, located on the rear of the truck body with different patterns for optimum safety during day and night for personal as well for traffic approaching from behind.

TECHNICAL DATA 2-45D	
Working width	1150mm
Shotblasting capacity	Up to 3000m ² /h on concrete or asphalt (depending on hardness, regulation requirements and pollution) -Up to 200m ² /h on steel
Drive system / speed	Hydraulic / 0 to 4.7 km/hr
Weight	1750kg (without side shift and drive unit)
Dimensions L / W / H	1250mm / 1300mm / 1300mm
Working speed	0,5 to 40 mtr/min
Application	Concrete / Asphalt / Steel

OPTIONS / ACCESSORIES	
20m suction hose Ø150	001112
Abrasive S390 / S460/ S550/ S660	999-0390 / 999-0460/ 999-0550/ 999-0660
2-20DT attachment	2-20DTA-UNIT
Magnetic broom R900	B22055
Fully automatic sweeper 2-45TBS	2-45TBS-0000
Personal safety features	On request / See manual

MAIN ASSETS

- Closed circuit which is dust free.
- Excellent separation system dust / abrasives by improved magnet separation system.
- High power hydraulic motors 2 x 30 kW.
- Versatile / Heavy duty / High performing machine.
- Magnetic separator, to perform well on sticky coatings and big quantities of dust.
- Optimal use on asphalt and concrete, but can also be used on steel.
- Homogenous blast pattern as well for light as heavy blasting purposes.
- Can be used for floor preparation / renovation / maintenance and decorative purposes.

