



## SHOTBLASTING MACHINE

## 1-8DPF40

| TECHNICAL DATA       |  |
|----------------------|--|
| Working width        | 203mm  |
| Blasting capacity    | Up to 70m <sup>2</sup> /h on concrete                    |
| Motor                | 4,0kW / 400V - 50Hz or 60Hz / 16A - Three phase - 5 pole |
| Weight               | 122 kg   |
| Dimensions L / W / H | 1.100 mm / 370mm / 1.030mm                               |
| Drive system / Speed | Electric / 0.5 - 23 m/min                                |
| Push / Pull machine  | Push   |
| Abrasive consumption | 10 - 75 gr/m <sup>2</sup>                                |
| Surface              | Steel / Concrete / Stone / Asphalt                       |

| OPTIONS / ACCESSORIES    |  |
|--------------------------|--|
| Dustcollector            | BDC-1330 / BDC-1330LP / BDC-1330LPP / BDC-3140LP / BDC-3140LPP |
| Abrasive S330 / S390     | 999-0330 / 999-0390  |
| 10m suction hose Ø76     | 005014   |
| Magnetic broom R600      | 001238   |
| Maintenance kit          | E07050 (50Hz) / E07051 (60Hz)                                  |
| Personal safety features | On request / See manual  |



**BDC-1330**



### MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Easy operating (walk behind).
- Can work very close to corners.
- Ergonomic design and user friendly control panel.
- Reliable machine, suitable for rental.
- Easy to transport, handle and use.
- Can be used for floor preparation / renovation / maintenance and decorative purposes.

FOR MORE INFORMATION VISIT [WWW.BLASTRAC.EU](http://WWW.BLASTRAC.EU)