



## SHOTBLASTING MACHINE

## 2-20DT

TECHNICAL DATA	
Working width	550mm
Blasting capacity	Up to 450m <sup>2</sup> /h on concrete
Motor	2 x 11kW / 400V - 50Hz or 60Hz / 63A - Three phase - 5 pole
Weight	575 kg
Dimensions L / W / H	1.950 mm / 720mm / 1.400mm
Drive system / Speed	Electric / 0.5 - 33 m/min
Push / Pull machine	Pull
Abrasive consumption	10 - 80 gr/m <sup>2</sup>
Surface	Steel / Concrete / Stone / Asphalt

OPTIONS / ACCESSORIES	
Dustcollector	BDC-655 / BDC-854 / BDC-955
Abrasive S330 / S390 / S460	999-0330 / 999-0390 / 999-0460
20m suction hose Ø150	001112
Magnetic broom R600	001238
Magnetic broom R900	B22055
Maintenance kit	E02035
Personal safety features	On request / See manual



**BDC-854**



### MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Highly versatile machine, appropriate for medium to big jobsite sizes.
- Very good performing and separation system.
- Powerful machine equipped with 11kW twin motors.
- Ergonomic design and user friendly control panel.
- Height adjusting system for easy transport.
- Very efficient on all types of floors.
- High performances and still fit to a standard door entrance.
- Increased productivity, reduced maintenance costs.
- Can be used for floor preparation / renovation / maintenance and decorative purposes.

FOR MORE INFORMATION VISIT [WWW.BLASTRAC.EU](http://WWW.BLASTRAC.EU)