



## SHOTBLASTING MACHINE

## 2-48DS

TECHNICAL DATA	
Working width	1.220mm
Blasting capacity	Up to 2.000m <sup>2</sup> /h on concrete (based on using 2-48DC)
Motor	2 x 22kW / 400V – 50 Hz / 125A – Three phase – 5 pole 2 x 25kW / 460V – 60 Hz / 125A – Three phase – 5 pole
Weight	1.350 kg
Dimensions L / W / H	2.420 mm / 1.433mm / 1.450mm
Drive system / Speed	Electric / 0 – 33 m/min
Push / Pull machine	Pull
Surface	Steel / Concrete / Stone / Asphalt

OPTIONS / ACCESSORIES	
Dustcollector	2-48DC
Abrasive S460 / S550 / S660	999-0460 / 999-0550 / 999-0660
20m suction hose Ø150	001112
Magnetic broom R900	B22055
Maintenance kit	On request
Personal safety features	On request / See manual



### MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Highly versatile machine, appropriate for big jobsite sizes.
- Special designed blast housing.
- Special developed heavy duty top/side liner system.
- Special separator flow adjustment system.
- Double rear wheels and idler system with gas spring cylinder system.
- 2 x 150mm dust hose connection for improved dust extraction.
- High performing and separation system.
- Powerful machine equipped with 2 blast motors.
- Ergonomic design and user friendly control panel.
- Very efficient on all types of floors.
- Increased productivity, reduced maintenance costs.
- Can be used for floor preparation / renovation / maintenance and decorative purposes.

FOR MORE INFORMATION VISIT [WWW.BLASTRAC.EU](http://WWW.BLASTRAC.EU)

Blastrac 06/2012 • This document is not contractual • Design and technical specifications may be subject to changes