# **BLASTRAC**

exbrite@exbrite.com

# **STEEL BLASTING MACHINE**

## 350VH

TECHNICAL DATA		
Working width	350mm	
Blasting capacity	Up to 40m <sup>2</sup> /h on steel SA 2,5	
Blast wheel power	11kW	
Drive system / Hoisting speed	Electric / 0,2 – 20 m/min	
Weight	600 kg	
Output motor	3 x 400V / 50Hz or 60Hz	
Electrical CEE plug	32A / Three phase – 5 pole	
Dimensions L / W / H	900 mm / 1.050mm / 1.250mm	
Abrasive consumption	0,2 - 0,5 kg/m <sup>2</sup>	
Application	Vertical steel	

## OPTIONS / ACCESSORIES

Dustcollector	BDC-655 / BDC-854	
Abrasive S390 / S460 / SG16 / SG25	999-0390 / 999-0460 / 999-0016 / 999-0025	
Suction hose Ø127 (minimum 30m)	492019	
Control standard	Remote control system	
Rigging systems	Cone Roof / Dome Roof / Floating Roof	
Winch system	Hydraulic / Electric hoisting	
Maintenance kit	On request	
Personal safety features	On request	BDC-854





### EXBRITE SURFACE FREFARATION EQUIPMENTS, ACCESSORIES AND DIAMOND TOOLS exbrite@exbrite.com

#### MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Hydraulic / Electrical hoisting system.
- Increased productivity, reduced maintenance costs.
- Fast and efficient removal of coatings, paint, rust, mill scale.
- Ergonomic design and user friendly remote control panel.
- Especially designed to be used on vertical steel surfaces like; oil / storage / water tank shells, ship hulls and many more.