

STEEL BLASTING MACHINE

600S

TECHNICAL DATA	
Working width	600mm
Blasting capacity	Up to 125m ² /h on steel
Blast wheel power	35kW
Drive system / Speed	Hydraulic / 1 – 30 m/min
Weight	1050 kg
Output motor	3 x 400V / 60Hz
Electrical CEE plug	63A / Three phase – 5 pole
Dimensions L / W / H	1.900 mm / 800mm / 1.820mm
Push / Pull machine	Push
Abrasive consumption	0,2 – 0,5 kg/m ²
Application	Steel

OPTIONS / ACCESSORIES	
Dustcollector	BDC-854 / BDC-955
Abrasive S460 / SG16 / SG25	999-0460 / 999-0016 / 999-0025
Suction hose Ø150 (minimum 20m)	001112
Maintenance kit	On request
Personal safety features	On request



BDC-854



EXBRITE

SURFACE PREPARATION EQUIPMENTS, ACCESSORIES AND DIAMOND TOOLS

exbrite@exbrite.com

MAIN ASSETS

- Closed circuit which is dust free, when connected to an appropriate Blastrac dust collector.
- Hydraulic drive system.
- Independent drive for each rear wheel.
- Increased productivity, reduced maintenance costs.
- The best performer for removal of thick-layers non-skid and epoxy coatings.
- Fast and efficient removal of coatings, paint, rust and mill scale.
- Ergonomic design and user friendly control panel.
- Especially designed to be used on ship decks, steel plates, platforms, oil platform helpdesks, oil platform walkways, smoke tracks, bridge decks, navy ship decks and steel floors.