



SCARIFYING MACHINE

BMP-265B

TECHNICAL DATA	
Working width	265mm
Scarifying capacity	Up to 120m ² /h on concrete
Motor power	8,2kW / Petrol
Working speed	1.500 rpm
Weight	175 kg
Dimensions L / W / H	1.260mm / 500mm / 1.160mm
Drive system / Speed	Manual / N/A
Push / Pull machine	Push
Surface	Concrete / Stone / Asphalt

OPTIONS / ACCESSORIES	
Dustcollector	BDC-1330 / BDC-1330LP / BDC-1330TLP
Drum complete with original cutters	MPD265SL272S
Drum complete with milling cutters	MPD265SL75S
Drum complete with full TC milling cutters	MPD265SL60S
Refill kit with original cutters	MPL272SL265
Refill kit with milling cutters	MPL75SL265
Refill kit with full TC milling cutters	MPL60SL265
10m Suction hose Ø76	005014
Personal safety features	On request / See manual



BDC-1330



MAIN ASSETS

- Closed circuit which is almost dust free, when connected to an appropriate Blastrac dust collector.
- Heavy weight for increased scarifying performances.
- New braking system with handle. During scarifying, the machine slows down itself. Brake force is easily changed with handle on steer.
- Extra heavy drum, for more down force.
- Adjustable braking device, lateral drum loading.
- Micrometric and memorized adjustment of the working depth: no underground deterioration and more precision.
- User friendly design, comfortable to use with low vibrations, easy to manoeuvre.
- Several optional cutting tools for each different application.

FOR MORE INFORMATION VISIT WWW.BLASTRAC.EU