




## SCARIFYING MACHINE

## BMP-335GHY

### TECHNICAL DATA

Working width	335mm
Scarifying capacity	Up to 150m <sup>2</sup> /h on concrete
Motor power	7,5kW / Diesel
Working speed	1.000 rpm
Weight	360 kg
Dimensions L / W / H	1.400mm / 605mm / 1.075mm
Drive system / Speed	Hydraulic / 1-15 m/min
Push / Pull machine	Push
Surface	Concrete / Stone / Asphalt

### OPTIONS / ACCESSORIES

Dustcollector	BDC-1330LP / BDC-1330LPP / BDC-3140LP / BDC-3140LPP	 <p><b>BDC-3140LP</b></p>
Drum complete (axle Ø22mm) with original cutters	MPD335-522L24S	
Drum complete (axle Ø22mm) with milling cutters	MPD335-522L29S	
Drum complete (axle Ø20mm) with full TC milling cutters	MPD335-620L60S	
Refill kit with original cutters	MPL24S335-5	
Refill kit with milling cutters	MPL29S335-5	
Refill kit with full TC milling cutters	MPL60S335-6	
10m Suction hose Ø76	005014	
Personal safety features	On request / See manual	



### MAIN ASSETS

- Closed circuit which is almost dust free, when connected to an appropriate Blastrac dust collector.
- Heavy weight for increased scarifying performances.
- New: drive system equipped with a pedal.
- When motor is on, machine is moving forward automatically, no need to push it.
- Adjustable braking device, lateral drum loading.
- Micrometric and memorized adjustment of the working depth: no underground deterioration.
- Variable speed, forward & backward motion.
- User friendly design, comfortable to use with low vibrations, easy to manoeuvre.
- Several optional cutting tools for each different application.

FOR MORE INFORMATION VISIT [WWW.BLASTRAC.EU](http://WWW.BLASTRAC.EU)

Blastrac 06/2012 • This document is not contractual • Design and technical specifications may be subject to changes